



Deutsche  
Qualität  
Garantiert



N-TYPE TOPCON TECHNOLOGY

# CMD-144BDS 560W-580W

More power, less degradation


**22.47%**  
MAXIMUM EFFICIENCY

**144**  
HALF CELLS


**30 YEARS** Performance Warranty      up to **30 YEARS\*** Product Warranty

\*The regular product warranty is 15 years, please refer to the latest version of AESOLAR Limited Warranty for the duration of the product warranty under special conditions. for extensions, please contact AESOLAR staff.

- LID RESISTANT
- PID RESISTANT
- SALT CORROSION RESISTANT
- SAND RESISTANT
- AMMONIA RESISTANT
- HIGHLY STABLE AND TOUGH



## OUR PERFORMANCE WARRANTY



## SYSTEM AND PRODUCT CERTIFICATIONS



IEC 61215 IEC 61730  
Regular Production Surveillance  
www.tuv.com  
ID 1111257249

IEC 62716 (Ammonia corrosion)  
IEC 61701 (Salt mist corrosion)  
IEC 60068 (Sand and dust)  
IEC 62804 (PID resistance)




www.ae-solar.com

# AE CMD-144BDS 560W-580W

N-TYPE TOPCON TECHNOLOGY PV MODULE

BIFACIAL • DOUBLE-GLASS



## Electrical specifications (STC\*):

	$P_{max}$ (Wp)	560	565	570	575	580
Nominal max. power	$P_{max}$ (Wp)	560	565	570	575	580
Maximum operating voltage	$V_{MPP}$ (V)	42.40	42.56	42.72	42.88	43.04
Maximum operating current	$I_{MPP}$ (A)	13.21	13.28	13.34	13.41	13.49
Open-circuit voltage	$V_{oc}$ (V)	50.38	50.49	50.62	50.73	50.86
Short-circuit current	$I_{sc}$ (A)	14.14	14.20	14.26	14.33	14.40
Module efficiency	$\eta$ (%)	21.70	21.89	22.08	22.28	22.47
Power tolerance	(W)	0~+5				
Maximum system voltage	(V)	1500				
Maximum series fuse rating	(A)	25				

\*STC: Standard Test Conditions (irradiance 1000 W/m², cell temperature 25°C and air mass of AM1.5), measurement tolerance  $P_{max}$ : ±3%

## Electrical specifications (NMOT\*):

	$P_{max}$ (Wp)	426.0	430.1	434.0	437.4	440.0
Nominal max. power	$P_{max}$ (Wp)	426.0	430.1	434.0	437.4	440.0
Maximum operating voltage	$V_{MPP}$ (V)	39.30	39.50	39.70	39.80	39.90
Maximum operating current	$I_{MPP}$ (A)	10.84	10.89	10.94	10.99	11.04
Open-circuit voltage	$V_{oc}$ (V)	47.50	47.70	47.80	48.00	48.20
Short-circuit current	$I_{sc}$ (A)	11.40	11.45	11.50	11.55	11.60

\*NMOT: Normal Module Operating Temperature (irradiance 800 W/m², ambient temperature 20°C, air mass of AM1.5 and wind speed of 1 m/s)

## Bifacial electrical specifications

Max. power front-side	560		565		570		575		580	
$P_{max}$ front (Wp)										
Backside Power Gain	5%	10%	5%	10%	5%	10%	5%	10%	5%	10%
Total equivalent power	588	616	593	622	598	627	604	633	610	639
$P_{max}$ equ (Wp)										
Module efficiency	22.79	23.87	22.99	24.09	23.18	24.29	23.39	24.51	23.62	24.75
$\eta$ (%)										

\*Bifacial Gain: The additional gain from the back side compared to the power of the front side at the standard test condition. It depends on the mounting (structure, height, tilt angle, etc.) and albedo of the ground.

## Mechanical and design specification

Cell type	n-Type TOPCon technology, half-cut cells
No. of cells	144
Bifaciality	80 ± 5%
Front cover	2.0 mm glass, high transmission, AR coated, tempered
Encapsulation	POE
Back cover	2.0 mm white glazed glass, tempered
Junction box	IP68 rated, 3 bypass diodes
Frame	30 mm anodized aluminium alloy
Cable	1 x 4 mm², 350 mm length or customized
Connectors	MC 4 / MC 4 compatible
Dimension	2278 mm x 1133 mm x 30 mm
Weight	31 kg
Hail resistance	Max. Ø 25 mm at 23 m/s
Wind load	2400 Pa or 244 kg/m²
Snow load	5400 Pa or 550 kg/m²
Fire rating	Class A (according to UL 790)

## Temperature ratings

Operating temperature	-40 to +85°C
Temp. coefficient of $P_{max}$	-0.29 %/°C
Temp. coefficient of $V_{oc}$	-0.25 %/°C
Temp. coefficient of $I_{sc}$	0.046 %/°C
Nom. operating cell temp. NOCT	42 ± 2°C

## Packaging information

Packaging configuration	36 pcs / pallet
Loading capacity	720 pcs / 40 HQ
Size / Pallet	2310 mm x 1140 mm x 1245 mm
Weight	1160 kg / pallet

The specifications and characteristics contained in this datasheet may deviate slightly from our actual products due to the product developments and uncertainty of measurement devices. The specifications included in the datasheet are subject to change without prior notice.